

# BV Series

# Specifications

## BV4160 Premium – BV4180 Premium



Kubota Models	BV4160	BV4180
<b>Weight and Dimensions</b>		
Length (in)	176"	176"
Width (in)	99"	99"
Height (in)	106"	112"
Weight (lbs)	5842	5952
<b>Bale chamber</b>		
Diameter Min (in)	31"	31"
Diameter Max (in)	65"	71"
Bale Width(in)	47"	47"
Bale Formation	5 Belts + 3 Rollers	
Endless Belts	-	-
Bale Ramp	•	•
<b>Pick-up</b>		
Working Width (in)	79"	79"
Number of Tine Rows	4	4
Tine Spacing (in)	2.36"	2.36"
Windguard	Crop Deflector	Crop Deflector
Pneumatic Gauge Wheel	•	•
<b>Intake System</b>		
Open Throat	-	-
Fork Feeder	•	•
SuperCut-14 Knives	-	-
Single Knife Protection	-	-
Knife Group Selection	-	-
Unblocking System	-	-
<b>Driveline</b>		
1 1/4" Chains	•	•
W-A PTO Shaft	•	•
Shear Bolt Protection	•	•
Cam Clutch Protection	•	•
<b>Binding</b>		
Twine (double) / Capacity	• / 8	• / 8
Net/Capacity	o / 3	o / 3
<b>Operations</b>		
ISOBUS	-	-
Focus Terminal	•	•
Alpha Bale Monitor	•	•
IsoMatch Tellus	-	-
Hydraulic Outlets	1SA + 1DA	1SA + 1DA
<b>Wheels and Axles</b>		
11.5/80-15	•	•
15.0/55-17	-	-
19.0/45-17	o	o
500/45-22.5	-	-
<b>Others</b>		
PTO (rpm)	540	540
Min. power requirem. (hp)	55	64

• = standard o = optional - = not available

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional and not standard equipment. Please consult your local Kubota dealer for warranty, safety or product information. For your safety, Kubota strongly recommend the use of a seat belt in all applications.